

# ENERGENCE® ULTRA-HIGH-EFFICIENCY UNITS

## ULTRA-HIGH-EFFICIENCY SPECIFICATIONS

		COOLING DATA		HEATING DATA (kBtuh)				PHYSICAL DATA			
NOM TON.	MODEL	EER	SEER OR IEER	LOW	STD.	MED.	HIGH	DIMENSIONS H X W X L [INCHES]	SHIP WT. [LBS.]		
GAS/ ELECTRIC UNITS	3	LGH036U4E	15.0	23.5	—	65	108	—	47 x 47 x 86	752	
	4	LGH048U4E	14.0	21.0	—	65	108	150	47 x 47 x 86	776	
	5	LGH060U4E	13.0	20.0	—	65	108	150	47 x 47 x 86	801	
	6	LGH074U4E	12.0	22.0	—	65	108	150	47 x 47 x 86	801	
	7.5	LGH094U4E/M	13.9/13.4	21.5/20.7	—	130	180	240	47 x 61 x 125	1,345	
	10	LGH0122U4E/M	13.1/12.6	20.0/19.2	—	130	180	240	47 x 61 x 125	1,355	
	12.5	LGH152U4E/M	12.3/12.0	18.9/18.1	—	130	180	240	47 x 61 x 125	1,365	
	15	LGH180U4M	12.7	20.2	169	260	360	480	55 x 92 x 133	2,590	
	20	LGH240U4M	12.0	20.0	—	260	360	480	55 x 92 x 133	2,630	
					KW RANGE						
ELECTRIC/ ELECTRIC UNITS	3	LCH036U4E	15.0	23.5	—	7.5	15	—	—	47 x 47 x 86	716
	4	LCH048U4E	14.0	21.0	—	7.5	15	—	—	47 x 47 x 86	740
	5	LCH060U4E	13.0	20.0	—	7.5	15	22.5	—	47 x 47 x 86	765
	6	LCH074U4E	12.0	22.0	—	7.5	15	22.5	—	47 x 47 x 86	765
	7.5	LCH094U4E/M	13.9/13.4	21.5/20.7	7.5	15	22.5	30	45	47 x 61 x 125	1,297
	10	LCH122U4E/M	13.1/12.6	20.0/19.2	15	22.5	30	45	60	47 x 61 x 125	1,307
	12.5	LCH152U4E/M	12.3/12.0	18.9/18.1	15	22.5	30	45	60	47 x 61 x 125	1,317
	15	LCH180U4M	12.7	20.2	15	30	45	60	—	55 x 92 x 133	2,440
	20	LCH240U4M	12.0	20.0	15	30	45	60	90	55 x 92 x 133	2,480