

Inserts Series Page 6

Grand

Rock and Glass

The only inserts you will find that encompass all of the most recent technology available including a full electronic package.

All inserts come standard with electronic ignition and there are two operating systems available to accommodate all application; the Deluxe and the Premier.

High 26,000BTU'S Low 13,000BTU'Min Clearances:

-Deluxe System requires 110V

-Premier System is battery powered


*Safety Screen attaches to unit



HD Log set

Both the Grand and the Champion inserts are true clean face design intended to maximize your viewing area.

Champion High 26,000BTU's Low 13,000BTU's Min Clearance



The Deluxe System boasts all the bells and whistles including a 7 day programmable remote with thermostat control and 7 stage modulating flame control. The Deluxe System also has a 6 stage modulating fan so the homeowner can enjoy both radiant and convection heat from one fireplace...

- -Deluxe System requires 110V
- -Premier System is battery powered

*Safety Screen attaches to unit

Accessories


Deluxe System *Standard for all Limited units/Option for all Elite units

- Electronic Ignition
- Fan Kit w/ 6 stage adjustable fan control
- Modulating flame control
- Deluxe remote w/ 7 day programmable thermostat

Basic Black Surround

Remote





DecorativeStainless Steel



Dimensional Chart and Features



Model	el BTU's		Vent Height		Width		Depth		Viewing Area		Efficiency	
	Natural Gas	Propane		Actual	Framing	Actual	Framing	Actual	Framing	Height	Width	EnerGuide
Coloot 12	Hi 30,000	29,000	Top	36"	42"	40-3/4"	45-3/4"	17-1/2"	19-1/2"	22 4/2"	24 4/4"	67.450/
Select 42	Lo 22,000	19,500	4" & 7"	36	43"	40-3/4	45-3/4	17-1/2	19-1/2	23-1/2	34-1/4	67.15%

Surrounds: Standard Features: Clean Face Design - 30,000BTU Full Deluxe System see page 5 Porcelain Liner Tempered Glass Traditional Log Set

 Basic Black 3 Sided Driftwood & Media Kits · Basic Stainless 3 Sided

Ch	ampion
-	

	Ins
	Standard
1	see page
01	O O



Model	BTU's		Vent Height		Width		Depth		Viewing Area		Efficiency	
	Natural Gas	Propane		Actual	Min	Actual	Min	Actual	Min	Height	Width	EnerGuide
Incort	Hi 26,000	23,000	Top	20.040*	20.4/4"	20.420*	27"	10 015"	16 1/4**	16"	25"	CO 200/
Insert	Lo 13,000	16,500	3" & 3"	20.049"	20-1/4"	30.129°	27"	18.215"	16-1/4"*	16"	25"	68.30%

see page 6 • True Clean Face Design • 26,000BTU • Electronic Ignition • Ceramic Brick Panel/Black Porcelain Panel • Your Choice of Either: Rock & Glass or				
2	True Clean Face Design	T		
	• 26,000BTU			
500 0300	Electronic Ignition	٦		
See page	Ceramic Brick Panel/Black Porcelain Panel			
U	Your Choice of Either: Rock & Glass or			
	Traditional 9pc Log Set			
	100% Safety Shut Off			

Surrounds: (Mandatory) Options: Standard Black Surround w/Safety Screen 26" High Deluxe System 110V Standard Black Surround w/Safety Screen 28" High Premier Battery Powered Standard 4 Sided Black Surround w/Safety Screen



Model	Model BTU's		Vent	Vent Height		Width		Depth		Viewing Area		Efficiency
	Natural Gas	Propane		Actual	Framing	Actual	Framing	Actual	Framing	Height	Width	EnerGuide
OD2000	Hi 40,000	32,500		25"	31"	12 1/0"	47-3/8"	14"	16"			
OD2000	Lo 29,000	24,000	Vent-less	25	31	43-1/0	47-3/6	14	10			

Options:

Standard Fe	atures:
	Linear Design
	 True Clean Face Or keep trim exposed
	• 40,000BTU
see page 5	All Stainless Steel
see bage s	Crisscross Stainless Steel Burner
	Remote Control
	 White Glass and River Pebble kit
	Cover with Kill Switch

 Driftwood #1,#2, or 3pcs 	
Media Kits	
Ceramic Stones	

